## For fast and efficient cutting of maximum strength rails.

- Short cutting times, e.g. approx. 1 min. possible for rail profile 49E1
- Flying sparks controlled downwards and optimum utilisation of cutting disc thanks to device changeover
- · Sturdy and light aluminium guide frame
- · Clamping device adjustable to rail type
- With kerf indicator for accurate determination of cutting point
- Relieves the operator thanks to supporting spring on the guide arm
- Easy starting of engine thanks to Smart Start decompression equipment
- Optimum filter effect due to air injection technology, fine filter and impregnated pre-filter
- · Spark protection for cutting disc continuously adjustable



SPECIFICATION			
Drive	2-stroke petrol engine	2-stroke petrol engine	2-stroke petrol engine
Туре	Husqvarna	Husqvarna	Husqvarna
Output	5.8 kW	5.8 kW	5.8kW
Cutting disc diameter	350 mm	400 mm	350 mm
Safety shut-down	yes	no	no
Cutting rate (*)	from 1 min/cut	from 1 min/cut	from 1 min/cut
	up to 8 cuts per disc	up to 10 cuts per disc	8 cuts per disc
Guide frame	from 9 kg	from 5.5 kg	from 5.5 kg
Engine powered cutter	from 18 kg	from 15.7 kg	from 15 kg
Cutting disc	from 0.8 kg	from 1.3 kg	from 0.8 kg
Total weight	from 27.8 kg	from 22.5 kg	from 21.3 kg

 $<sup>(\</sup>ensuremath{^\star})$  depending on rail profile, cutting disc and operator etc.

## **ACCESSORIES**

## **Cutting discs**

9002000309 Ø 350 x 4 x 22.2 mm 9002000300 Ø 350 x 4 x 25.4 mm 9002000911 Ø 400 mm x 4 mm x 25

9002000911 Ø 400 mm x 4 mm x 25.4 mm

Other cutting discs on request.

9000860394 Adapter for cutting discs with 25.4 mm holder

for 13.70, EDP no:

87099000318709900033

not necessary for 13.70 with EDP no.:

• 8709900030

8001381004 ROBEL 13.81 Safety Blocking Device for cutting

rails under compressive stress, incl. 1 pair of wedges

8708960100 Transport box

9801370182 Guide frame for grooved rails for 13.70 with EDP no.:

• 8709900033

• 8709900031





