

For precise grinding of welding joints and for reprofiling the complete rail head. Can also be used in switches, for frogs and for grinding grooved rails.

THE ADVANTAGES. YOUR BENEFITS.

Leight-weight machine. Powerful grinding results.

- Excellent view of the cup wheel and rail
- High machine availability thanks to durable clutch
- Low maintenance of the machine (e.g. simple starter rope replacement on the construction site, protection of the spindle against grinding dust)
- Sturdy stainless steel tank
- Easy changing of cup wheel thanks to Quick Lock
- Rotational resistance can be adjusted at spindle hand wheel without the use of any tools

Easy operation. Safe working.

- · Ergonomic use due to low centre of gravity
- Side stand for safe placement of machine (left-hand guide handle)
- Exhaust gas routing away from operator, even when side grinding
- LED lighting

TECHNICAL SPECIFICATION	
Drive	One-cylinder 4-stroke engine (Honda)
Туре	RGX200
Output	4.6 kW
Weight	from 55 kg
Roller spacing	850 mm
Dimensions (L x W x H)	1080 x 515 x 765 mm

ACCESSORIES

5158930018 Extension arm

5158930019 Additional rollers for grooved rails and switches

Cup wheels

9002000687 Ø 125 mm central nut holder M20

