

ROPOWER 76.20 E³ High-Pressure Power Pack-Battery

Emission-free power for hydraulic weld trimmers and hydraulic rail stressors.

THE ADVANTAGES. YOUR BENEFITS.

Compact design

- Low space requirement for transport and storage
- Frame protects components from damage
- Carrying handle options (2-part, 4-part)

Quick and easy working

- Automatic changeover from low pressure range to high pressure range
- Keyed connectors prevent misconnection
- Use in urban areas, tunnels and open cast mining
- Flexible use of various ROBEL batteries
- Use of a second rail stressor possible due to integrated shut-off valves in the hose kit
- Use of the 2300 Wh battery or a power supply (with adapter) possible
- 400 Wh battery: approx. 15-20 trimming operations or approx. 7 stressing operations
- 800 Wh battery: approx. 28-32 trimming operations or approx. 14 stressing operations



ROPOWER 76.20 – 5089900002
4-part carrying handles – 5088930001
ROBATTERY 71.01 800 Wh – 7806800004

SPECIFICATION	SINGLE	DUAL
Drive	BLDC electric motor	BLDC electric motor
Output	1.3 kW	1.3 kW
Pressure supply	550 bar	550 bar + 670 bar
Dimensions (L x W x H)	605 x 365 x 395 mm	605 x 365 x 395 mm
Weights		
Hydraulic power pack (without carrying handles, without battery)	32 kg	38 kg
Battery 400 Wh	3.9 kg	3.9 kg
Battery 800 Wh	6.3 kg	6.3 kg
Drive for	ROTRIM 14.10	ROTRIM 14.10+ ROSTRESS 24.70
Emergency hand pump no yes	no	yes (optional)

ACCESSORIES

- 7826800002 Battery 400 Wh
- 7806800004 Battery 800 Wh
- 7806850001 Charger for 400/800 Wh battery
- 9000208016 Battery box for battery 800 Wh
- 5088930001 4-part carrying handles
- 5088930002 2-part carrying handles
- 9000860451 Hose kit ROTRIM 14.10 Hydraulic Weld Trimmer
- 5087900005 Hose kit ROSTRESS 24.70 Hydraulic Rail Stressor
- 5088930003 Distribution block for operating 2 rail stressors (ROSTRESS 24.70)

