

ROCUT 13.86 Rail Cutter

For efficient cutting of maximum strength rails.

- Rail can be cut from both sides without changeover
- Relieves the operator thanks to supporting spring on the guide arm
- Precise positioning at the cutting point due to kerf indicator
- Easy starting of engine thanks to Smart Start decompression equipment
- Optimum filter effect due to air injection technology, fine filter and impregnated pre-filter
- Electronic speed limiter
- Centrifugal clutch
- Spark protection of cutting disc continuously adjustable
- Sturdy and light aluminium guide frame
- Optional: available with safety shutdown



SPECIFICATION

Drive	2-stroke petrol engine	2-stroke petrol engine
Type	Husqvarna	Husqvarna
Output	5.8 kW	5.8 kW
Cutting disc diameter	300 mm	350 mm
Cutting rate (*)	from 1 min/cut up to 6 cuts/cutting disc	from 1 min/cut up to 8 cuts/cutting disc
Weight		
Rail Cutter	from 16 kg	from 16.8 kg
Guide frame	from 11.2 kg	from 11.2 kg
Cutting disc	from 0.5 kg	from 0.8 kg
Total weight machine	from 27.7 kg	from 28.8 kg

(*) depending on rail profile, cutting disc and operator etc.

ACCESSORIES

Cutting discs

9002000307 ø 300 x 3.5 x 22.2 mm

9002000309 ø 350 x 4 x 22.2 mm

9002000300 ø 350 x 4 x 25.4 mm

Other cutting discs on request.

8394150100 Adapter for cutting discs with 25.4 mm holder

8001380010 Clamping device for grooved rails
(max. head width 130 mm)

8001380020 Guide frame, complete, for grooved rails

8001381004 Safety blocking device ROBEL 13.81
for cutting rails under compressive stress
incl. 1 pair of wedges

8398960100 Transport box