

ROLIGHT KLL

For extensive lighting of work sites.

Special compact fluorescent lamps with high output at low current consumption. 4 of the 8 lamps can be turned off, providing glarefree light in one direction.

- Illuminated area of up to 700 m
- Can withstand wind speeds of up to 120 km/h due to special stand
- Saves space and quick to set up
- Safe delivery and storage in impact-resistant flight case

SPECIFICATION

Diameter	200 mm
Length	900 mm
Optimum height in use	3500 mm
Number of lamps	8 x 80 W
Output	0,36 – 0,7 kW*
Supply voltage	230 VAC
Required generator power (230 VAC)	1,0 kW
Total weight	ab 41,4 kg

* depending on operating mode



ROLIGHT KLL - 9807306104

ROLIGHT LED

For lighting work sites.

Available versions with one, two or four lamps. Low current consumption at high luminosity.

- Maintenance-free
- Can be used in flexible temperature range: -40 C to +55 C
- No UV/IR radiation
- Extendable from 1000 to 3500 mm
- Can be folded down to 1000 x 190 x 190 mm

SPECIFICATION

LED output	0.04 kW
Voltage	230 VAC
LED service life	> 50,000 h
Total weight	from 15 kg



ROLIGHT LED - 9807306102