

## ROCARRY 42.10 Rail Carrying Roller Tongs

For lifting and loading/unloading rails

- Self-clamping
- With locking device to prevent the tongs from releasing autonomously



### SPECIFICATION

Max. carrying capacity	0.5 t	1.5 t	1.5 t	3 t
Suitable for	small flat bottom rails	flat bottom rails	conductor rails	flat bottom rails
Dimensions (L x W x H)	200 x 170 x 230 mm	270 x 165 x 300 mm	270 x 165 x 290 mm	270 x 220 x 300 mm
Weight	from 6.5 kg	from 16 kg	from 14 kg	from 24.7 kg
Rollers	4	4	4	6

## ROCARRY 42.11 Rail Carrying Tongs

For lifting and transporting rails

- ROLOAD 40.44 and 40.51 rail loader
- With locking device to prevent the tongs from releasing autonomously

### SPECIFICATION

Max. carrying capacity	1.5 t	3 t
Suitable for	flat bottom rails	
Dimensions (L x W x H)	100 x 165 x 300 mm	
Weight	from 5.4 kg	



## ROCARRY 42.22 Rail Carrying Tongs with Suspension Eye

For lifting and transporting rails

- With suspension eye (crane hook securing) and locking device
- Sturdy design with 3 lifting claws
- Opens automatically when touching down on rail head
- Different versions available for different rail types.  
Get in touch with your ROBEL contact

### SPECIFICATION

Max. carrying capacity	3 t
Dimensions (L x W x H)	120 x 130 x 400 mm
Weight	from 10.9 kg

